



# 4230

EMERGENCY SHOWERS AND EYEWASHES - SHOWERS / EYEWASHES

## Pedestal Shower and Eyewash, ABS shower head / bowl, includes spray unit



### GENERAL FEATURES

*MATERIALS:* Galvanized steel piping. Brass fittings.

*ANTICORROSIVE PLASTIC COATING:* Polyamide with a thickness of 250-300 microns, in high-visibility yellow color.

*WATER INLET:* Female thread ISO 228 G1-1/4"

*WATER INLET PRESSURE:* Recommended 2 bar / Min. 1.5 bar / Max. 8 bar

### SHOWER

*MATERIALS:* Shower head in ABS plastic.

*FLOW RATE:* Regulated at 110 l/min.

*OPERATION:* Pull rod.

*VALVE:* Full bore valve 1"

### EYEWASH

*MATERIALS:* Eyewash assembly and Eyewash bowl in ABS plastic. Two high-flow aerated water sprays at low pressure with automatic opening anti-dust cover.

*FLOW RATE:* Regulated at 22 l/min.

*OPERATION:* Push handle.

*VALVE:* Full bore valve 1/2"

*WASTE:* Female thread ISO 228 G1-1/4"

### DRENCH HOSE

*MATERIALS:* High-flow aerated water spray at low pressure with automatic opening anti-dust cover.

*FLOW RATE:* Regulated at 15 l/min.

*OPERATION:* Lever.

### PACKING

*Weight:* 19 kg

*Dimensions:* 76 x 27 x 22 cm