



4255

EMERGENCY SHOWERS AND EYEWASHES - SHOWERS / EYEWASHES Pedestal Shower and Eyewash with foot control, ABS shower head / bowl, includes spray unit



GENERAL FEATURES

MATERIALS: Galvanized steel piping. Brass fittings. ANTICORROSIVE PLASTIC COATING: Polyamide with a thickness of 250-300 microns, in high-visibility yellow color. WATER INLET: Female thread ISO 228 G1-1/4" WATER INLET PRESSURE: Recommended 2 bar / Min. 1.5 bar / Max. 8 bar

SHOWER

MATERIALS: Shower head in ABS plastic. FLOW RATE: Regulated at 110 l/min. OPERATION: Pull rod. VALVE: Full bore valve 1"

EYEWASH

MATERIALS: Eyewash assembly and Eyewash bowl in ABS plastic. Two highflow aerated water sprays at low pressure with automatic opening anti-dust cover.

FLOW RATE: Regulated at 22 l/min. OPERATION: Push handle / Foot treadle VALVE: Full bore valve 1/2" WASTE: Female thread ISO 228 G1-1/4"

DRENCH HOSE

MATERIALS: High-flow aerated water spray at low pressure with automatic opening anti-dust cover. FLOW RATE: Regulated at 15 l/min. OPERATION: Lever.

PACKING Weight: 20 kg Dimensions: 76 x 27 x 22 cm

