



# 4255 SS

EMERGENCY SHOWERS AND EYEWASHES - SHOWERS / EYEWASHES

**Pedestal Shower and Eyewash with foot control, SS shower head / bowl, includes spray unit**



## GENERAL FEATURES

*MATERIALS: Galvanized steel piping. Brass fittings.*

*ANTICORROSIVE PLASTIC COATING: Polyamide with a thickness of 250-300 microns, in high-visibility yellow color.*

*WATER INLET: Female thread ISO 228 G1-1/4"*

*WATER INLET PRESSURE: Recommended 2 bar / Min. 1.5 bar / Max. 8 bar*

## SHOWER

*MATERIALS: Shower head in stainless steel.*

*FLOW RATE: Regulated at 110 l/min.*

*OPERATION: Pull rod.*

*VALVE: Full bore valve 1"*

## EYEWASH

*MATERIALS: Eyewash assembly in ABS plastic. Eyewash bowl in stainless steel. Two high-flow aerated water sprays at low pressure with automatic opening anti-dust cover.*

*FLOW RATE: Regulated at 22 l/min.*

*OPERATION: Push handle / Foot treadle*

*VALVE: Full bore valve 1/2"*

*WASTE: Female thread ISO 228 G1-1/4"*

## DRENCH HOSE

*MATERIALS: High-flow aerated water spray at low pressure with automatic opening anti-dust cover.*

*FLOW RATE: Regulated at 15 l/min.*

*OPERATION: Lever.*

## PACKING

*Weight: 21 kg*

*Dimensions: 76 x 27 x 22 cm*