4295 SS

EMERGENCY SHOWERS AND EYEWASHES - SHOWERS / EYEWASHES

Shower and drench hose double spray Eyewash, wall mounting, SS shower head



GENERAL FEATURES

MATERIALS: Galvanized steel piping. Brass fittings.

ANTICORROSIVE PLASTIC COATING: Polyamide with a thickness of 250-300 microns, in high-visibility yellow color.

WATER INLET: Female thread ISO 228 G1"

WATER INLET PRESSURE: Recommended 2 bar / Min. 1.5 bar / Max. 8 bar

SHOWER

MATERIALS: Shower head in stainless steel.

FLOW RATE: Regulated at 110 l/min.

OPERATION: Pull rod.

VALVE: Full bore valve 1"

DRENCH HOSE EYEWASH

MATERIALS: Two high-flow aerated water sprays at low pressure with automatic opening anti-dust cover.

FLOW RATE: Regulated at 22 l/min.

OPERATION: Lever.

PACKING

Weight: 11 kg

Dimensions: 141 x 27 x 13 cm

C/ Compositor Narváez 10, Pol. Ind. Can Jardi, 08191 Rubí / Barcelona (España)
Tel: +34 935 860 780 · Email: infoweb@carlosarboles.com
Skype: carlos.arboles · (Horario 9h00 a 17h00 GMT+1) · NIF: A08866055