



# 2240

EMERGENCY SHOWERS AND EYEWASHES - EYEWASHES

## Pedestal Eyewash, ABS bowl, includes spray unit



### GENERAL FEATURES

*MATERIALS: Galvanized steel piping. Brass fittings.*

*ANTICORROSIVE PLASTIC COATING: Polyamide with a thickness of 250-300 microns, in high-visibility yellow color.*

*WATER INLET: Male thread ISO 228 G1/2"*

*WATER INLET PRESSURE: Recommended 2 bar / Min. 1.5 bar / Max. 8 bar*

### EYEWASH

*MATERIALS: Eyewash assembly and Eyewash bowl in ABS plastic. Two high-flow aerated water sprays at low pressure with automatic opening anti-dust cover.*

*FLOW RATE: Regulated at 22 l/min.*

*OPERATION: Push handle.*

*VALVE: Full bore valve 1/2"*

*WASTE: Female thread ISO 228 G1-1/4"*

### DRENCH HOSE

*MATERIALS: High-flow aerated water spray at low pressure with automatic opening anti-dust cover.*

*FLOW RATE: Regulated at 15 l/min.*

*OPERATION: Lever.*

### PACKING

*Weight: 7.5 kg*

*Dimensions: 80 x 27 x 13 cm*