4730 TI

EMERGENCY SHOWERS AND EYEWASHES - SHOWERS / EYEWASHES

Shower and Eyewash platform in stainless steel, independent operation

Self-draining



GENERAL FEATURES

MATERIALS: Piping and fittings in stainless steel.

WATER INLET: Female thread ISO 228 G1-1/4"

WATER INLET PRESSURE: Recommended 2 bar / Min. 1.5 bar / Max. 4 bar

SHOWER

MATERIALS: Shower head in stainless steel.

FLOW RATE: Regulated at 110 l/min.

OPERATION: Pull rod.

VALVES: Special valve (automatic drain) + Full bore valve 1"

EYEWASH

MATERIALS: Eyewash assembly in stainless steel. Two high-flow aerated water sprays at low pressure with automatic opening anti-dust cover.

FLOW RATE: Regulated at 22 l/min.

OPERATION: Entering the platform.

VALVE: Special valve (automatic drain)

PACKING

Weight: 38 kg

Dimensions: 102 x 86 x 13 cm

C/ Compositor Narváez 10, Pol. Ind. Can Jardi, 08191 Rubí / Barcelona (España)
Tel: +34 935 860 780 · Email: infoweb@carlosarboles.com
Skype: carlos.arboles · (Horario 9h00 a 17h00 GMT+1) · NIF: A08866055