



4700 SS

EMERGENCY SHOWERS AND EYEWASHES - SHOWERS / EYEWASHES

Shower and Eyewash double platform, independent operation, SS shower head / bowl

Self-draining



GENERAL FEATURES

MATERIALS: Galvanized steel piping. Brass fittings.

ANTICORROSIVE PLASTIC COATING: Polyamide with a thickness of 250-300 microns, in high-visibility yellow color.

WATER INLET: Female thread ISO 228 G1-1/4"

WATER INLET PRESSURE: Recommended 2 bar / Min. 1.5 bar / Max. 4 bar

SHOWER

MATERIALS: Shower head in stainless steel.

FLOW RATE: Regulated at 110 l/min.

OPERATION: Entering the platform.

VALVE: Special valve (automatic drain)

EYEWASH

MATERIALS: Eyewash assembly in ABS plastic. Eyewash bowl in stainless steel. Two high-flow aerated water sprays at low pressure with automatic opening anti-dust cover.

FLOW RATE: Regulated at 22 l/min.

OPERATION: Entering the platform.

VALVE: Full bore valve 1/2"

WASTE: Female thread ISO 228 G1-1/4"

PACKING

Weight: 71 kg

Dimensions: 102 x 86 x 13 cm (2x)