



# 4730 FP

EMERGENCY SHOWERS AND EYEWASHES - SHOWERS / EYEWASHES

**Shower and Eyewash platform, independent operation, underground water supply, ABS shower head**

*Self-draining, Extreme temperature protection*



## GENERAL FEATURES

*MATERIALS: Galvanized steel piping. Brass fittings.*

*ANTICORROSIVE PLASTIC COATING: Polyamide with a thickness of 250-300 microns, in high-visibility yellow color.*

*WATER INLET: Female thread ISO 228 G1-1/4"*

*WATER INLET PRESSURE: Recommended 2 bar / Min. 1.5 bar / Max. 4 bar*

## SHOWER

*MATERIALS: Shower head in ABS plastic.*

*FLOW RATE: Regulated at 110 l/min.*

*OPERATION: Pull rod.*

*VALVES: Special valve (automatic drain) + Full bore valve 1"*

## EYEWASH

*MATERIALS: Eyewash assembly in ABS plastic. Two high-flow aerated water sprays at low pressure with automatic opening anti-dust cover.*

*FLOW RATE: Regulated at 22 l/min.*

*OPERATION: Entering the platform.*

*VALVE: Special valve (automatic drain)*

## PACKING

*Weight:*

*Dimensions: 102 x 86 x 13 cm (1x) 141 x 27 x 13 cm (1x)*