



4223 FP

EMERGENCY SHOWERS AND EYEWASHES - SHOWERS / EYEWASHES

Shower and Eyewash, independent operation, ABS shower head / bowl, underground water supply

Self-draining, Extreme temperature protection



GENERAL FEATURES

MATERIALS: Galvanized steel piping. Brass fittings.

ANTICORROSIVE PLASTIC COATING: Polyamide with a thickness of 250-300 microns, in high-visibility yellow color.

WATER INLET: Female threads ISO 228 G1-1/4" + G1/2"

WATER INLET PRESSURE: Recommended 2 bar / Min. 1.5 bar / Max. 8 bar

SHOWER

MATERIALS: Shower head in ABS plastic.

FLOW RATE: Regulated at 110 l/min.

OPERATION: Push handle.

VALVE: Full bore valve 1-1/4" (automatic drain)

EYEWASH

MATERIALS: Eyewash assembly and Eyewash bowl in ABS plastic. Two high-flow aerated water sprays at low pressure with automatic opening anti-dust cover.

FLOW RATE: Regulated at 22 l/min.

OPERATION: Push handle.

VALVE: Full bore valve 1/2" (automatic drain)

WASTE: Female thread ISO 228 G1-1/4"

PACKING

Weight: 45 kg

Dimensions: 191 x 32 x 12 cm (2x) 76 x 27 x 22 cm (1x)