



# 4223 FP/SS

EMERGENCY SHOWERS AND EYEWASHES - SHOWERS / EYEWASHES

**Shower and Eyewash, independent operation, SS shower head / bowl, underground water supply**

*Self-draining, Extreme temperature protection*



## GENERAL FEATURES

**MATERIALS:** Galvanized steel piping. Brass fittings.

**ANTICORROSIVE PLASTIC COATING:** Polyamide with a thickness of 250-300 microns, in high-visibility yellow color.

**WATER INLET:** Female threads ISO 228 G1-1/4" + G1/2"

**WATER INLET PRESSURE:** Recommended 2 bar / Min. 1.5 bar / Max. 8 bar

## SHOWER

**MATERIALS:** Shower head in stainless steel.

**FLOW RATE:** Regulated at 110 l/min.

**OPERATION:** Push handle.

**VALVE:** Full bore valve 1-1/4" (automatic drain)

## EYEWASH

**MATERIALS:** Eyewash assembly in ABS plastic. Eyewash bowl in stainless steel. Two high-flow aerated water sprays at low pressure with automatic opening anti-dust cover.

**FLOW RATE:** Regulated at 22 l/min.

**OPERATION:** Push handle.

**VALVE:** Full bore valve 1/2" (automatic drain)

**WASTE:** Female thread ISO 228 G1-1/4"

## PACKING

**Weight:** 46 kg

**Dimensions:** 191 x 32 x 12 cm (2x) 76 x 27 x 22 cm (1x)