



# 4221 SS

EMERGENCY SHOWERS AND EYEWASHES - SHOWERS / EYEWASHES

## Low ceiling pedestal Shower and Eyewash, SS shower head / bowl



### GENERAL FEATURES

*MATERIALS: Galvanized steel piping. Brass fittings.*

*ANTICORROSIVE PLASTIC COATING: Polyamide with a thickness of 250-300 microns, in high-visibility yellow color.*

*WATER INLET: Female thread ISO 228 G1-1/4"*

*WATER INLET PRESSURE: Recommended 2 bar / Min. 1.5 bar / Max. 8 bar*

### SHOWER

*MATERIALS: Shower head in stainless steel.*

*FLOW RATE: Regulated at 110 l/min.*

*OPERATION: Pull rod.*

*VALVE: Full bore valve 1"*

### EYEWASH

*MATERIALS: Eyewash assembly in ABS plastic. Eyewash bowl in stainless steel. Two high-flow aerated water sprays at low pressure with automatic opening anti-dust cover.*

*FLOW RATE: Regulated at 22 l/min.*

*OPERATION: Push handle.*

*VALVE: Full bore valve 1/2"*

*WASTE: Female thread ISO 228 G1-1/4"*

### PACKING

*Weight: 19 kg*

*Dimensions: 76 x 27 x 22 cm*